

# TECHNICAL DATA SHEET

## S2 EXTRA SHINE HOLOGRAM REMOVER



### Finishing Compound



#### PRODUCT DESCRIPTION

Finishing compound S2 EXTRA SHINE HOLOGRAM REMOVER can be used by professionals and DIY as a finishing product in polishing process. Thanks to S2 we will get higher gloss on surface and remove holograms.

#### PRODUCT INFORMATION

SURFACE TYPE	gelcoat, paints and varnishes
EFFECT	Removal of holograms and micro-scratches, effect of mirror surface and deep gloss
CATEGORY	Production, DIY
PRODUCT TYPE	finishing
COLOR	white
DENSITY	0,965 kg/l
CONSISTENCY	Liquide-cream
METHODE OF POLISHING	Machine, manual
MACHINE TYPE	rotary machine, orbital machine
APPLICATOR	lamb wool type MM, soft sponges type FINISH, microfiber cloth
CUT LEVEL	 2/10
GLOSS LEVEL	 10/10

#### INSTRUCTION FOR USE

SURFACE PREPARATION	Wash surface using Sea-Line S3 FINISH CLEANER SHINE CONTROL. If removing defects from surface is necessary, grind it and finish sanding on minimal gradation P3000. Remove dust after sanding. Once again wash surface using S3
ONE STEP PROCESS	Apply finishing compound S2 onto surface or applicator. Starts polishing from the lowest rotation speed (800-1000 RPM) until compound starts to change color Slowly increase rotation speed to max. 2000 RPM. Polish until all defects are removed and full gloss obtained. Remove dust and all residues left from polishing process using S3 FINISH CLEANER If necessary repeat polishing process.
FURTHER WORK	For Surface protection use: <ul style="list-style-type: none"><li>• Sea-Line® S4 WAX or Sea-Line® S5 QUICK WAX</li></ul> For daily maintenance use: <ul style="list-style-type: none"><li>• Sea-Line C3 SHAMPOO WITH WAX</li></ul>
IMPORTANT NOTES	The elements that have influence on end effect are: <ul style="list-style-type: none"><li>• Surface preparation by choosing correction gradation of sand papers</li><li>• Applicator type</li></ul> Details on <a href="http://www.sea-line.eu">www.sea-line.eu</a>

#### STORAGE AND SAFETY INFORMATION

SHELF LIFE	24 months from production
------------	---------------------------

# TECHNICAL DATA SHEET

## S2 EXTRA SHINE HOLOGRAM REMOVER

### Finishing Compound

---



STORAGE	Product components should be stored in tightly sealed containers, in a temperature of 10-25°C, away from sources of fire, heat and sunlight. Close container tightly immediately after each use. Store in a dry place and keep sealed cans until use. Keep away from children. Protect from frost.
HSE CONDITIONS	Please follow safety instructions from the Safety Data Sheet and follow workplace safety laws. The general rule is to avoid contact of the product with the skin and eyes. Notice ! Always follow all precautionary, health and safety notice on the Safety Data Sheet and container labels.
DISCLAIMER	All data in this document have been prepared for informational purpose only. We can not take responsibility for the results of user actions over which we have no control. The user is responsible for making the control sample and determining the suitability of the product for specific, individual applications. Company Troton Sp. z o.o. does not take responsibility for any damage, or loss of profits associated with the improper use of the products. All information is based on scrupulous laboratory research and many years of experience. Our position of market leadership does not free us from constant quality control of our products. However, we do not accept responsibility for the effects of improper use or storage of our products, or the effects of using our products in any way contrary to the standard of good workmanship.
QUALITY QUARANTEE	Production, quality control and the realization of deliveries fulfill the demands of ISO 9001 and 14001 standards.