

Technical Data Sheet

THINNER FOR POLYURETHANE TOPCOATS AND VARNISH -SPRAY



PRODUCT DESCRIPTION

Thinner for polyurethane is a mixture of specially combined organic solvents. It is dedicated for Sea-Line Polyurethane topcoats and varnish. It allows to get final product of clearly defined parameters, provides proper application, leveling and curing. Detailed ratios for each product are given on TDS.

PRODUCT INFORMATION

COLOR transparent
DENSITY 0,890kg/liter
METHODE OF APPLICATION spray

INSTRUCTION FOR USE

PRODUCT PREPARATION Thinner is not sell in set with topcoat or varnish. Choose proper thinner to application method. First mix base with hardener keeping mixing proportion, than add thinner in proper proportion.

THINNING

Polyurethane Clear Coat 2:1

Function	spray
Primer	15-20%
Topcoat	0-5%

Polyurethane 2:1 color

Color	spray
White	45-50%
Ecru	
Red	
Navy blue	
Blue	
Green	
Grey	
Black	

STORAGE AND SAFETY INFORMATION

SHELF LIFE 12 months from production date

STORAGE Product components should be stored in tightly sealed containers, in a temperature of 10-25°C, away from sources of fire, heat and sunlight. Close container tightly immediately after each use. Store in a dry place and keep sealed cans until use.

HSE CONDITIONS Please follow safety instructions from the Safety Data Sheet for hazardous chemical and follow workplace safety laws. The general rule is to avoid contact of the product with the skin and eyes. When product is used in a small, closed spaces you must provide forced ventilation. It is also recommended that you protect your respiratory system,

Technical Data Sheet

THINNER FOR POLYURETHANE TOPCOATS

AND VARNISH -SPRAY



eyes, and skin. Special care should be taken in the area of fire protection and explosion hazards. **Notice ! Always follow all precautionary, health and safety notice on the Safety Data Sheet and container labels.**

DISCLAIMER

All data in this document have been prepared for informational purpose only. We can not take responsibility for the results of user actions over which we have no control. The user is responsible for making the control sample and determining the suitability of the product for specific, individual applications. Company Troton Sp. z o.o. does not take responsibility for any damage, or loss of profits associated with the improper use of the products. All information is based on scrupulous laboratory research and many years of experience. Our position of market leadership does not free us from constant quality control of our products. However, we do not accept responsibility for the effects of improper use or storage of our products, or the effects of using our products in any way contrary to the standard of good workmanship.

QUALITY GUARANTEE

Production, quality control and the realization of deliveries fulfill the demands of ISO 9001 and 14001 standards.