

COLOR RENOVATION

PRODUCT FOR RESTORING COLOUR



Technical information

Product components:

Sea-Line® COLOR RENOVATION – 1 - component

Volume :

500 ml

Product description :



Sea-Line® COLOR RENOVATION does not contain silicone, it is a product which restores the original look and brightness of material:

- gelcoat .
- polyurethane paint and others
- plastic
- metal (chrome, brass, steel, stainless steel, aluminum, bronze)
- stone (marble, terracotta, tiles).

Sea-Line COLOR RENOVATION penetrates deeply surface and re-wetting pigments, restoring color and brightness which have been lost through exposure to sunlight, rain and pollution.

Using Color Renovation we can restore matt surface and chulky.

COLOR RENOVATION protect surface against corrosion, on the surface leaves protective layer, there is no need using protecting wax. Easy in use.

Notice : Do the test use on white – colored syrfaces.

Physiochemical characteristic :

Physical state :

liquid

Colour:

amber (transparent)

Fragrance:

specific

Weight :

870 g/l

Solid content:

32÷35 %

Theoretical output:

16÷20 m²/l depending on the surface

Metod of application:

brush, microfibre cloth,

Preparing the surface

- Remove wax and other polishes product
- Wash surface using C2 Sea-Line Concentrate Cleaner
- Surface must be dry and should not have contact with water, fog, dew before application COLOR RENOVATION at least 12 hours.
- Protect white surface against COLOR RENOVATION
- Apply on the surface quantity which you can used in time 20 minutes.
- Apply COLOR RENOVATION Sea-Line® on the surface using brush or microfibre cloth
- Leave COLOR RENOVATION Sea-Line® on the surface for 20 minutes.
- Remove excess COLOR RENOVATION Sea-Line® from the surface.
- Allow to dry.

Further work :

- After 24 hours to increase shine we can polish surface using microfibre cloth.
- To remove defects we can polish surface using polishing compound S1 Sea-Line or finishing compound S2 Sea-Line.
- Recommended surface protection
 - S5 Sea-Line Quick Wax
 - S4 Sea-Line Protect Wax

COLOR RENOVATION

PRODUCT FOR RESTORING COLOUR



Technical information

HSE condition:

If swallowed immediately seek medical advice and show label of product.

Storage :



Store in a closed container at the temperature between 5 - 35 °C.

Store away from fire, heat and UV rays.

Close the packaging after every use.

Store away from children.

Expiration date :

24 months from the date of production in temperature 20°C.

Quality Guarantee :

Production, quality control, and the realization of deliveries fulfill the demands of ISO 9001 and 14001 standards.

All data in this document have been prepared for informational purposes. We can not take responsibility for the results of user actions over which we have no control. Responsibility of the user is to make the test sample and determine the suitability of the product for individual applications. Sea-Line do not take responsibility for any damages, or loss of profits associated with the improper use of the products.

All information is based on scrupulous laboratory research and many years of experience. Our position of market leadership does not free us from constant quality control of our products. However, we do not accept responsibility for the effects of improper use or storage of our products, or for the effects of using our products in any way contrary to the standards of good workmanship.

TROTON sp. z o.o. Zabrowo.