

SEA-LINE BRAYT S05

ONE STEP, HEAVY CUT & GLOSS

Polishing compound



Technical information

Product components: Sea-Line® S05 POLISHING COMPOUND
ONE STEP, HEAVY CUT & GLOSS
one-component product

Packaging: 1 kg,

Product description and use:



Sea-Line® S05 polishing compound is a one-stage compound with a high cutting force which guarantees quick removal of defects and grinding scratches from a surface after treatment with sandpaper of gradation from P800.

Sea-Line® S05 polishing compound is primarily designed for the companies which produce goods in which the outer layer is gelcoat or forms made from utility gelcoat and an industrial topcoat with a high toughness degree.

Using S05 compound allows for shortening the labour time thanks to a high cutting force while obtaining appropriate gloss on the surface without the necessity of using other kinds of polishing compounds.

Technical data:

Cutting force:  9 /10

Gloss level:  8 /10


Physical and chemical properties:

Density: 1,42 kg/l
Colour: White
Texture: PASTE
Working : Rotary Machine, hand

Application methods: Rotation polishing machine,
lambswool, hard sponge

Application conditions: Product works best at the temperature 15~25°C

Surface preparation and method of use:



- Clean the surface destined for polishing
- If removing defects is necessary, polish the surface with sandpaper of the following gradation:
 - final polishing: <P800
 - final polishing (dark colours): <P1200
- Clean the surface again
- Apply the compound onto an element or head (wool or tough sponge)
- Apply the compound at minimum rotations on the whole surface that is being polished (800-1000 rotations/min) polishing until it changes colour and the compound changes its texture
- Slowly increase the speed max. to 1800 RPM working with a little pressure.
- Polish until all defects are removed and full gloss is obtained.
- If necessary, repeat the polishing process.

SEA-LINE BRAYT S05 ONE STEP, HEAVY CUT & GLOSS Polishing compound



Technical information

Further steps:

After changing the applicator to a head made of 100% lambswool (MM Sea-Line BRAYT) or a soft sponge, polish the surface for obtaining higher gloss.

In order to enhance the level of gloss, it is also recommended to use:

- Sea-Line® S2 FINISHING COMPOUND

In order to protect the surface, it is recommended to use:

- Sea-Line® S5 QUICK WAX
- Sea-Line® S4 PROTECT WAX

H&S rules:

In case of swallowing, consult your doctor immediately and show the container label.

Storage:



Store in a closed container at the temperature between 0 - 35°C.

Store away from fire, heat and UV rays. Przechowywać daleko od źródła ognia, ciepła oraz promieniowania UV.

Protect from frost.

Close the packaging after every use.

Store away from children.

Shelf life:



24 months from the date of production

Quality Guarantee:

Production, quality control, and the realization of deliveries fulfill the demands of ISO 9001 and 14001 standards.

All data in this document have been prepared for informational purposes. We can not take responsibility for the results of user actions over which we have no control. Responsibility of the user is to make the test sample and determine the suitability of the product for individual applications. Sea-Line do not take responsibility for any damages, or loss of profits associated with the improper use of the products.

All information is based on scrupulous laboratory research and many years of experience. Our position of market leadership does not free us from constant quality control of our products. However, we do not accept responsibility for the effects of improper use or storage of our products, or for the effects of using our products in any way contrary to the standards of good workmanship.

TROTON sp. z o.o. Ząbrowo.