

MATERIAL SAFETY DATA SHEET

Prepared according to the Decree of European Council no. 1907/2006 from 18.12.2006 regarding registering, evaluation, certification and authorizations in range of chemicals (REACH), creation of European Chemicals Agency, changing Directive 1999/45/EC and cancelling decree of Council no. 793/93 and decree of Commission no.1488/94, as well as directives 76/769/EC, 91/155/EC, 93/67/EC, 93/105/EC and 2000/21/EC.

SECTION 1 IDENTIFICATION OF THE PREPARATION AND OF THE COMPANY/UNDERTAKING1.1. Product identifier:**SELF-POLISHING ANTIFOULING ALU-PLUS**1.2. Relevant identified uses of the substance or mixture and uses advised against:

Professional repairs of car body repairs.

1.3. Details of the supplier of the safety data sheet:

Manufacturer/Distributor

TROTON Sp. z. o. o.

78-120 Gościno

Ząbrowo, 14A, Poland

Tel./Fax: + 48 94 35 126 22

Tel.: + 48 94 35 123 94

E-mail: troton@troton.com.pl

1.3.1. Responsible person; E-mail: troton@troton.com.pl

1.4. Emergency telephone number: + 48 94 35 126 22 (from 8:00 am – 4:00 pm)**SECTION 2 IDENTIFICATION OF THREATS**2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or Directive 1999/45/EC:

Flammable (R10). Contact with acids liberates very toxic gas (R32). Harmful (Xn). Harmful by inhalation, in contact with skin and if swallowed (R20/21/22). Irritating (Xi). Risk of serious damage to eyes (R41). May cause sensitization by skin contact(R43). Irritating to skin (R38). Dangerous for the environment (N). Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment (R50/53).

Classification according to Regulation (EC) No 1272/2008:

H226 Flammable liquids, Hazard Category 3

H302 Acute toxicity (oral), Hazard Category 4

H312 Acute toxicity (dermal), Hazard Category 4

H315 Skin corrosion/irritation, Hazard Category 2

H317 Sensitisation — Skin, Hazard Category 1

H318 Serious eye damage/eye irritation, Hazard Category 1

H332 Acute toxicity (inhal.), Hazard Category 4

H400 Hazardous to the aquatic environment — AcuteHazard, Category 1

Label elements :

GHS07



GHS02



GHS09



Signal Word: WARNING!

Hazard Statement (H)::

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

Precautionary Statement (P):

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container according to the local regulations.

Contain: Copper thiocyanate 400g/l Pyrrithione zinc 40g/l

2.3. Information concerning particular hazards for human and environment:

Inhalation: in mild cases it causes cough, irritation of the mouth and throat, sometimes it causes chest pain. In more acute cases it causes headache, vertigo, fatigue, maysthenia, drowsiness and in extreme cases loss of consciousness.

Eye contact: causes mechanical irritation, redness, pain and asthenopia. If the drops of the product get in the eyes, may cause impairment of sight and allergic reactions.

Skin contact: may cause irritation. In case of problematic skin, skin absorption may occur. In case of long term or repeated contact the skin drying and erythroderma may occur. Irritation and redness may occur.

Chronic exposure:

In case of chronic inhalation of the vapour/dust of the product, chest pain, irritation of the mucous membranes, headache, vertigo, excitement or drowsiness, problems with the digestive system, exsiccation, cracking of the skin and allergy may occur.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Mixture:

Description	CAS No	EU No	EEC No	(%)	Classification			
					REACH		CLP	
					Hazard symbol	R phrase	Hazard cat.	H phrase
Copper thiocyanate	1111-67-7	214-183-1	---	25-50	Xn	R32 R20/21/22	Acute Tox. 4 Acute Tox. 4 Acute Tox. 4	H332 H312 H302
Xylene	1330-20-7	215-535-7	601-022-00-9	10-25	Xn Xi	R10 R20/21 R38	Flam. Liq. 3 Acute Tox. 4 Acute Tox. 4 Skin Irrit. 2	H226 H332 H312 H315
rosin; colophony	8050-09-7	232-475-7	650-015-00-7	5-10		R43	Skin Sens. 1	H317
Zinc oxide 01-2119463881-32	1314-13-2	215-222-5	030-013-00-7	5-10	N	R50-53	Aquatic Acute1 Aquatic Chronic1	H400 H410
Pyrrithione zinc	13463-41-7	236-671-3	---	1-5	T Xn Xi N	R23 R22 R41 R38 R50	Acute Tox. 3 Acute Tox. 3 Eye Dam. 1 Skin Irrit. 2 Aquatic Chronic 2	H301 H331 H318 H315 H400
Tritolyl phosphate (m-m-m-, m-m-p-, m-p-p-, p-p-p-)	78-32-0	201-105-6	015-016-00-3	0-1	Xn N	R21/22 R51-53	Acute Tox. 4 Acute Tox. 4 Aquatic Chronic 2	H312 H302 H411
Hydrocarbons, C10, aromatics, <1% naphthalene	---	918-811-1	---	1-5	Xn N	R65 R66 R67 R51/53	Asp. Tox. 1 Aquatic Chronic 2	H304 H411
1-methoxy-2-propanol	107-98-2	203-539-1	603-064-00-3	0-1	--	R10 R67	Flam. Liq. 3 STOT SE 3	H226 H336

Full meaning of phrases and symbols are in section 16.

SECTION 4 FIRST AID MEASURES

4.1. Description of first aid measures:

Take normal precautionary measures applied during the handling of chemicals. In case of any symptoms, seek medical advice.

IN CASE OF INGESTION:

Measures:

- If swallowed, do not induce vomiting (risk of aspiration).
- Obtain immediate medical help.

IN CASE OF INHALATION:

Measures:

- Remove the affected person to fresh air, keep calm, cover with a blanket.

- In case of shortness of breath, give oxygen.
- If breathing has stopped, administer artificial respiration and obtain medical help.

IN CASE OF SKIN CONTACT:**Measures:**

- Immediately flush with plenty of water.
- Take off all contaminated clothing.
- Wash skin with plenty of water and soap.
- In case of symptoms, obtain medical attention and show him the label!

IN CASE OF EYE CONTACT:**Measures:**

- Remove contact lenses.
- Flush immediately with plenty of water for 15 minutes, holding the eyelids wide open.
- Consult an ophthalmologist.

4.2. Most important symptoms and effects, both acute and delayed:

Inhalation: in mild cases it causes cough, irritation of the mouth and throat, sometimes it causes chest pain. In more acute cases it causes headache, vertigo, fatigue, myasthenia, drowsiness and in extreme cases loss of consciousness.

Eye contact: causes mechanical irritation, redness, pain and asthenopia. If the drops of the product get in the eyes, may cause impairment of sight and allergic reactions.

Skin contact: may cause irritation. In case of problematic skin, skin absorption may occur. In case of long term or repeated contact the skin drying and erythroderma may occur. Irritation and redness may occur.

Chronic exposure:

In case of chronic inhalation of the vapour/dust of the product, chest pain, irritation of the mucous membranes, headache, vertigo, excitement or drowsiness, problems with the digestive system, exsiccation, cracking of the skin and allergy may occur.

4.3. Indication of any immediate medical attention and special treatment needed:

No special antidote, apply symptomatic treatment.

SECTION 5 FIRE-FIGHTING MEASURES**5.1. Extinguishing media:****5.1.1. Suitable extinguishing media:**

Foam, carbon dioxide or dry chemical.

5.1.2. Unsuitable extinguishing media:

Strong water jet.

5.2. Special hazards arising from the substance or mixture:

In case of combustion, carbon oxide and toxic fumes are formed.

5.3. Advice for firefighters:

Wear full protective clothing (gas-tight and antistatic) and self-contained breathing apparatus.

Cool the fire affected containers with water spray.

Prevent penetration into ground and surface water. Prevent penetration of the fire extinguishing media into ground and surface water. Collect fire extinguishing media separately, do not discharge into sewage system.

SECTION 6 ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures:****6.1.1. For non-emergency personnel:**

Keep unprotected people away, allow only well trained experts wearing suitable protective clothing to abide in the field of accident.

6.1.2. For emergency responders:

Remove all ignition sources, flames.

Protect sewage outlets.

Disperse vapours with water spray.

Stop leakage – close the source of the leakage, seal damaged container and place in an other container.

Ensure adequate ventilation.

Wear protective clothing and gloves.

Do not inhale vapours.

6.2. Environmental precautions:

Dispose of spillage and waste (product/packaging) in accordance with all applicable environmental laws. Do not allow to enter sewers/soil/surface or ground water. Notify the respective authorities in accordance with local law in the case of environmental pollution immediately.

6.3. Methods and material for containment and cleaning up:

Absorb the spilled product with an inert substance (e.g.: sand or diatomaceous earth) and transfer into a sealed container, and send to an authorized waste disposal company. During disposal wear suitable personal protective equipment.

6.4. Reference to other sections:

For further and detailed information see section 8 and 13.

SECTION 7 HANDLING AND STORAGE

- 7.1. Precautions for safe handling:
 Observe conventional hygiene precautions.
 Avoid contact with skin and eyes.
 Do not inhale vapours.
 Do not eat, drink or smoke during the usage.
 Technical measures:
 Use only in well-ventilated places with exhaust ventilation.
 Tools, equipments and containers must be sealed tightly.
 Precautions against fire and explosion:
 Keep away from heat and ignition sources.
- 7.2. Conditions for safe storage, including any incompatibilities:
 Technical measures and storage condition:
 Keep in original, tightly closed and labelled container.
 The place of storage has to be properly ventilated and cleanable.
 Store in cool and dry place.
 Protect against sunlight.
 Store below 20°C.
 Do not store with self-igniting substances and peroxides.
 Store in original, properly labelled containers, which are tightly sealed.
 Do not smoke, eat, use open fire and sparking tools in the place of the storage.
 Keep away from the reach of children.
 Follow all instructions on the label.
 Incompatible materials: strong oxidizing agents.
 Packaging material: original container.
- 7.3. Specific end use(s):
 No specific instructions available.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1. Control parameters:
- | Substance name | CAS Nr. | 8 hours | Short term |
|----------------|-----------|--------------------------------|--------------------------------|
| Xylene | 1330-20-7 | 221 mg/m ³ , 50 ppm | 442mg/m ³ , 100 ppm |
- 8.2. Exposure controls:
 In case of a hazardous material with no controlled concentration limit it is the employer's duty to keep concentration levels down to a minimum achievable by existing scientific and technological means, where the hazardous substance poses no harm to workers.
- 8.2.1 Appropriate engineering controls
 In pursuance of work is proper foresight needed to avoid spilling onto clothes and floors and to avoid contact with eyes and skin.
 The suction of the vapours at the source(s) of emission and general exhaust ventilation is required. The exhaust vents should be placed in the upper part of the room and at the floor level.
 Keep away from heat and ignition sources.
- 8.2.2 Individual protection measures, such as personal protective equipment:
1. Eye/face protection: When working with the product, wear safety glasses with side protection (like goggles) to protect against splashes or a full face shield for protection against vapours and aerosols
 2. Skin protection:
 - a. Other: wear suitable protective clothing made of dense fabric. To prevent skin drying, use suitable protective cream. Separate private clothes from work clothes. Contaminated clothes can not be reused without prior cleaning (washing).
 - b. Other: wear suitable protective clothing made of dense fabric. To prevent skin drying, use suitable protective cream. Separate private clothes from work clothes. Contaminated clothes can not be reused without prior cleaning (washing).
 3. Respiratory protection: In case of insufficient ventilation, wear suitable respiratory protection - protective filter masks adapted to activities associated with processing of the product.
 4. Thermal hazard: None known.
- 8.2.3 Environmental exposure controls:
 No specific prescription.
 The requirements detailed in Section 8 assume skilled work under normal conditions and usage of the product for appropriate aims.
 If conditions differ from normal or work is carried out under extreme conditions an expert's advice should be sought out before deciding upon further protective measures.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES:

9.1. Information on basic physical and chemical properties

Physical condition/form colour	Liquid of high viscosity; white
Odour	No data
Boiling point	No data
Melting point:	No data
Vapours pressure	No data
Solubility in water and other solvents	In water: insoluble
Solubility in organic solvents	Well soluble
Specific gravity	No data
pH:	No data
Ignition temperature	27°C
Explosive properties: limits	No data
Autoignition point	No data
Flammable	No data available
Explosive properties: limits	Not explosive, no concern
Oxidizing properties	Not oxidizing, no concern
Distribution ratio 1-n-octanol/water	No data available
Other properties:viscosity	ISO (2431:1993) 6mm:>60s

9.2. Other information:
Denisty : 1,32 g/ cm³

SECTION 10 STABILITY AND REACTIVITY

- 10.1. Reactivity:
None known.
- 10.2. Chemical stability:
At normal temperature: stabile at general conditions of work.
- 10.3. Possibility of hazardous reactions:
None known.
- 10.4. Conditions to avoid:
High temperature, fire.
- 10.5. Incompatible materials:
storg oxidizing agents.
- 10.6. Hazardous decomposition products:
In case of high temperature or fire, carbon oxides and toxic smoke may evolve.
-

SECTION 11 TOXICOLOGICAL INFORMATION

- 11.1. Information on toxicological effects:
Acute toxicity: Harmful by inhalation and in contact with skin.
Irritation: None known.
Corrosivity: None known.
Sensitisation: None known.
Repeated dose toxicity: Repeated exposure may cause skin dryness or cracking.
Carcinogenicity: None known.
Mutagenicity: None known.
Reproduction toxicity: None known.
- 11.1.1. For substances subject to registration, brief summaries of the information derived from the test conducted:
No data available.
- 11.1.2. Relevant toxicological properties of the hazardous substances:
Information on toxicological effects:

<i>Name of the substance:</i>	<i>CAS-number:</i>	<i>Dose:</i>	<i>Value:</i>	<i>Unit:</i>
1-methoxy-2-propanol	107-98-2	LD ₅₀ (rat, dermal)	> 10000	mg/kg
		LD ₅₀ (rat, oral)	> 5000	mg/kg
Xyelne	1330-20-7	LD50(rat, dermal)	4300	mg/kg
		LD50(rat, oral)	22100	mg/m ³ /4h
Pyrithione zinc	13463-41-7	LD50(rat, dermal)	>2000	mg/kg
		LD50(rat, oral)	269	mg/m ³ /4h

		LD50(rat, inhalation)	1,03	mg/kg
11.1.3.	Information on likely routes of exposure: ingestion, inhalation, skin and eye contact.			
11.1.4.	Symptoms related to the physical, chemical and toxicological characteristics: Inhalation: in mild cases it causes cough, irritation of the mouth and throat, sometimes it causes chest pain. In more acute cases it causes headache, vertigo, fatigue, maysthenia, drowsiness and in extreme cases loss of consciousness. Eye contact: causes mechanical irritation, redness, pain and asthenopia. If the drops of the product get in the eyes, may cause impairment of sight and allergic reactions. Skin contact: may cause irritation. In case of problematic skin, skin absorption may occur. In case of long term or repeated contact the skin drying and erythroderma may occur. Irritation and redness may occur. Chronic exposure: In case of chronic inhalation of the vapour/dust of the product, chest pain, irritation of the mucous membranes, headache, vertigo, excitement or drowsiness, problems with the digestive system, exsiccation, cracking of the skin and allergy may occur.			
11.1.5.	Delayed and immediate effects as well as chronic effects from short and long-term exposure: Harmful by inhalation and in contact with skin. Repeated exposure may cause skin dryness or cracking.			
11.1.6.	Interactive effects: No data available.			
11.1.7.	Absence of specific data: No information.			
11.1.8.	Other information: No data available.			

SECTION 12 ECOLOGICAL INFORMATION

- 12.1. Toxicity:
Aquatic toxicity:

Name of the substance:	CAS-number:	Method:	Value:	Unit:
Xyelne	1330-20-7	LC50-ryby (salmo gairdneri)	3,77	mg/l/96h
		LC50-algi Daphnia magna	10-100	mg/l/96h
		EC50-bakterie	>100	mg/l

Effect on activated sludge: at proper entering of small concentrations to biological sewage treatment plants no perturbations should be expected during the decomposition of the activated sludge.

- 12.2. Persistence and degradability:
No data available.
- 12.3. Bioaccumulation potential:
No data available.
- 12.4. Mobility in soil:
No data available.
- 12.5. Results of PBT and vPvB assessment:
No data available.
- 12.6. Other adverse effects:
No data available.

SECTION 13 DISPOSAL CONSIDERATIONS

- 13.1. Waste treatment methods:
Disposal according to the local regulations.
- 13.1.1. Information regarding the disposal of the product:
Do not dispose with communal wastes, do not pour into drainage system. Incinerate in specially adapted installations or deliver to authorized waste collector.
European Waste Catalogue code:
08 01 00 wastes from MFSU and removal of paint and varnish
08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
* hazardous waste.
- 13.1.2. Information regarding the disposal of the packaging
Used packaging should be delivered to authorized collector who has due permission within the range of waste management and especially in dangerous waste management.
European Waste Catalogue code:
For used packaging:
15 01 10* packaging containing residues of or contaminated by dangerous substances
* hazardous waste.

- 13.1.3. Physical/chemical properties that may affect waste treatment options shall be specified:
None known.
- 13.1.4. Sewage disposal:
None known.
- 13.1.5. Special precautions for any recommended waste treatment:
No data available.

SECTION 14 TRANSPORT INFORMATION

Land transport (ADR/RID)

UN Number UN1263
 UN proper shipping name PAINT
 Transport hazard class(es) 3
 Label: 3
 Hazard identification number: 30



Packing group III.
 Environmental hazards YES see 5.2.1.8 Agreement ADR
 Tunnel restriction code (D/E)

Marine transport IMDG/IMO

UN Number UN1263
 UN proper shipping name PAINT
 Transport hazard class(es) 3
 Label: 3



EmS code F-E,S-E
 Packing group III.
 Environmental hazards YES, see 5.2.1.6 IMDG Code

Air transport IATA

UN Number UN1263
 UN proper shipping name PAINT
 Transport hazard class(es) 3
 Label: 3
 Hazard identification number: 30



Packing group III.
 Environmental hazards YES, see 7.1.7 IATA Dangerous Goods Regulation
 Special precautions for user No data available.

SECTION 15 REGULATORY INFORMATION

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture:
 REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC
 COMMISSION REGULATION (EC) No 790/2009 of 10 August 2009 amending, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures
 DIRECTIVE 1999/45/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 May 1999 concerning the approximation of the laws, regulations and administrative provisions of the Member States relating to the classification, packaging and labelling of dangerous preparations
 REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

15.2. Chemical safety assessment: -

SECTION 16 OTHER INFORMATION

Information regarding the revision of the safety data sheet: -

Full text of the abbreviations in the safety data sheet:

DNEL: Derived no effect level. PNEC: Predicted no effect concentration. CMR effects: carcinogenicity, mutagenicity and toxicity for reproduction: PBT: Persistent, bioaccumulative and toxic. . n.d.: not defined. . n.a.: Not applicable. .

Data sources: -

Relevant R-Phrases (number and full text) of Section 2 and 3:

R10 Flammable

R20/21 Harmful by inhalation and in contact with skin

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed

R21/22 Harmful in contact with skin and if swallowed

R22 Harmful if swallowed

R23 Toxic by inhalation

R32 Contact with acids liberates very toxic gas

R36/38 Irritating to eyes and skin

R38 Irritating to skin

R41 Risk of serious damage to eyes

R43 May cause sensitization by skin contact

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R65 Harmful: may cause lung damage if swallowed

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapours may cause drowsiness and dizziness

Relevant H-Phrases (number and full text) of Section 2 and 3:

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled..

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects..

H411 Toxic to aquatic life with long lasting effects.

EUH 205 – Contains epoxy constituents. May produce an allergic reaction.

Abbreviations of the hazard categories:

Acute Tox. 4 Acute toxicity

Aquatic Acute1 Hazardous to the aquatic environment

Aquatic Chronic 2 Hazardous to the aquatic environment

Aquatic Chronic1 Hazardous to the aquatic environment

Asp. Tox. 1 Acute toxicity

Carc. 1B Carcinogenicity

Eye Irrit. 2 Serious eye damage/eye irritation

Flam. Liq. 3 Flammable liquid

Lact. Reproductive toxicity

Skin Irrit. 2 Skin corrosion/irritation

Skin Sens. 1 Respiratory/skin sensitization

Training instructions: -

Recommended restrictions on use (non-statutory recommendations by supplier): -

This safety data sheet had been prepared on the basis of information provided by the manufacturer. The information, data and recommendations contained herein are provided in good faith, obtained from reliable sources and believed to be true and accurate as of the date issued; however, no representation is made as to the comprehensiveness of the information. The MSDS shall be used only as a guide for handling the product; in the course of handling and using the product other considerations may arise or be required. Since the conditions or the handling, the storage and the disposal of this product are beyond the control of the manufacturer, the distributor or the preparer of this SDS, no warranty, expressed or implied, regarding the product described in this

MSDS shall be created or inferred by any statement in this SDS. No responsibility is assumed regarding the accuracy, completeness or suitability of all or any of the information contained herein or the results to be obtained from the use thereof at the time of use. In no way shall the manufacturer, the distributor or the preparer of the be liable for any claims, losses or damages of third parties, personal injury, property damage, lost profits or any special, direct, indirect, incidental, consequential or exemplary damages resulting from the use of or reliance upon such information. Users are cautioned to determine the appropriateness and applicability of the above information to their particular circumstances and purposes and assume all risk associated with the use of this product. It is the responsibility of the user to fully comply with local, national and international regulations concerning the use of this product.