

SEA-LINE BRAYT S1 POLISHING COMPOUND



Technical information

Product components : Polishing compound S1 – one pack product

Volume: Single pack: 500 g

Product description :



Sea-Line® S1 is a very effective polishing product which does not contain silicone. Recommended for polishing boats, gelcoat surfaces, products from composites, and topcoats. S1 quickly removes defects after sanding with sandpaper as well as other exploitation damages, and guarantees obtaining an ideal surface. Includes high-quality polishing minerals, which ensures quick removal of defects and achieving a high gloss through a one-stage process.

Recommended use:


It is a universal product, appropriate for every kind of gelcoat, PE and PU varnishes in the furniture industry and in the manufacturing of products made of composites. Thanks to an optimal composition, the product does not cause excessive heating of a surface, being easy to clean at the same time. By working with Sea-Line® S1 we save our time.

Physiochemical Characteristics:

Density : 1,21 kg/l
Color: turquoise

Cut level:

Gloss level



Preparing the surface:



- Wash the work surface.
- sanding with a sandpaper of granulation :
 - general sanding : P320 ÷ P800
 - finishing sanding : P1200 ÷ P1500 (dark colors P1500 ÷ P200).
- Remove dust and degrease again.
- Wash the work surface other contaminations with fresh water.

Method of application: Lamb wool, hard sponge or medium-hard sponge,

Application conditions: Product works best when its temperature is 15 – 25°C

Application:

- Apply compound on the surface to be treated (use: lambs wool / hard sponge / medium-hard sponge).
- Spread compound on the surface by machine with minimum RPM (800 to 1000).
- Polish surface with medium pressure.
- Slowly increase RPM (1200 – 1500) until polish surfaces until the scratches have been removed.
- Increase RPM (max 2000) and polish to reach perfect gloss.

Further Work :

Change applicator to pad made from 100% natural lambswool (Type MM Sea-Line® BRAYT) or a soft sponge and polish to reach perfect gloss. For increase shine effect please use:

- finishing compound S2

to protect the surface use :

- S4 Protect wax
- S5 Quick wax

Storage :



Storage in sealed container at 0 – 35°C

Product components should be kept in tightly sealed containers, in dry and cool spaces, far away from the sources of flames, heat, and sun rays.

Caution: After every use, containers should be closed immediately!

SEA-LINE BRAYT S1 POLISHING COMPOUND



Technical information

| | |
|----------------------------|---|
| Expiration date : | 24 months from production date |
| Quality Guarantee : | Production, quality control, and the realization of deliveries fulfill the demands of ISO 9001 and 14001 standards. |
| Quality Guarantee : | Production, quality control, and the realization of deliveries fulfill the demands of ISO 9001 and 14001 standards. |

All data in this document have been prepared for informational purposes. We can not take responsibility for the results of user actions over which we have no control. Responsibility of the user is to make the test sample and determine the suitability of the product for individual applications. Sea-Line do not take responsibility for any damages, or loss of profits associated with the improper use of the products.

All information is based on scrupulous laboratory research and many years of experience. Our position of market leadership does not free us from constant quality control of our products. However, we do not accept responsibility for the effects of improper use or storage of our products, or for the effects of using our products in any way contrary to the standards of good workmanship.

TROTON sp. z o.o. Ząbrowo.